

Key Features

- Implemented antimicrobial technology on pen and housing
- High performance and e-Signature precision with 2048 pen pressure
- Ergonomic design, VESA compliance, and Kensington lock security
- Windows® compatible and supports e-Signature software
- 8H tempered glass with anti-scratch, anti-glare, and anti-fingerprint



Product Description

ViewSonic PD1013 is an ideal solution for optimizing the user experience with streamlined service via Kiosk solution. 10.1-inch LCD pen display offers intuitive writing, annotating, and signage capabilities for organizations that need to let customers use in portrait and landscape mode, making it easier for the user to view and sign documents. It's an ideal e-Signature solution for corporate, banking, finance, hospitality, insurance, and healthcare.

Visit Us

www.viewsonic.com

LCD PANEL

Display Area:	216.96 x 135.6 mm (10.1" TFT LCD)
Optimum Resolution:	1280 x 800 pixels
Brightness:	200 cd/m2
Contrast Ratio:	800:1
Backlight:	LED Light-Bar
Viewing Angles:	H:170° (85°/ 85°) V:170° (85°/ 85°)
Panel Surface:	Anti-glare, Hard coating (8H)

CONNECTOR

USB:	Micro USB 2.0 x 1
------	-------------------

TOUCH

Accuracy:	+/- 0.5mm(center)
-----------	-------------------

ERGONOMICS

Tilt:	Portrait : 0/ 15°/ 20° Landscape: 0/ 9°/ 13°
-------	---

COMPATIBILITY

PC:	Windows 10, 11, and later (Win 7, Linux Ubuntu, Chrome OS by request)
-----	--

POWER

Voltage:	USB 5V
Consumption:	4.55W (Typ.) / 5.06W (Max.)

OPERATING CONDITIONS

Temperature (° F / ° C):	0°C to 50°C
Humidity:	20%-80%(Max), Non-condensation

DIMENSIONS W X H X D (INCH/MM)

Physical (in / mm):	287.0 x 185.6 x 14.3 mm
Box (in / mm):	350.0 x 273.0 x 76.0 mm

WEIGHT

Net (lb / kg):	0.66 kg
Gross (lb / kg):	1.09 kg

REGULATIONS

CE/ FCC/ BSMI

WARRANTY

1 Year

WHAT'S IN THE BOX

1. PD1013 Pen display x 1
2. USB 2.0 2-in-1 Y-cable (Micro USB to Type A x 2) x 1
3. EMP-001 Pen x 1
4. Pen nib x 3
5. Pen tether x 1
6. Nib removal tool x 1
7. Screwdriver x 1
8. AC/DC Power adapter 5V/2A x 1
9. Quick start guide x 1